

ASX

Technical Specifications

Pressure ulcer grade ● I ● II ● III ● IV

Max. patient weight 140 kg

Item No. ASX DS 997008DS / 103722

Control unit

Measurements 30 x 18 x 12 cm

Weight 2.7 kg

Features Membrane compressor, digital control with pressure sensor, alternating pressure, static mode (CLP), time cycle (12 min.), 5 m connection cable with IEC connector and cable strain relief,
NEW: touchpad control panel

Alarm functions In case of low pressure and/or failure of the cycle change, there is an audible and visual alarm,
NEW: with power failure alarm (visual and audible)

Mattress overlay

Measurements 200 x 88 x 13 cm (inflated, without base mattress)

Weight 5.4 kg

Material cells High-quality nylon PU cell material

Material cover PES polyurethane cover with all-round zip, bi-elastic, breathable, slip-retardant

Features 18 cells, 3 static head cells, non-bending connecting tubes (incl. transportation safety lock), CPR emergency ventilation, cable management system



The ASX control unit features digital pressure sensor technology, ensuring quiet operation and a long product life.

The redesigned control unit has a touchpad display and a removable IEC plug. The smooth, low-joint surface can be completely wiped down with disinfectant, preventing bacteria from accumulating behind mechanical controls. The compressors switch off automatically when the preset system pressure is reached and only activate when there are cycle changes or to adjust the system pressure.

The ASX mattress overlay has nylon/PU cells; the cover is bi-elastic, PU-coated and equipped with an all-round zip. In addition, a double-layer base allows the insertion of a safety mattress up to 5 cm thick, thus protecting the existing mattress from dirt.

Highlights

- Long service intervals
- Low noise level
- Hygienic touchpad
- Easy disinfection
- Digital pressure sensor technology
- Energy-efficient operation
- All-round zip fastener

For other mattress sizes and optional accessories – see pricelist.

