

# ProLift Cacero

## Technical Specifications

Max. patient weight	180 kg
<b>Item No.</b>	960800N H / 101365 – Euro plug 960805N HU / 101366 – 3 pin UK plug
Castors	Front: 2 x 75 mm double, rear: 2 x 100 mm single with brake
Hoisting capacity	180 kg
Hoisting height	695 – 1845 mm
Size of undercarriage	W x L x H: 595 x 1150 x 95 mm
Sling bar length	542 mm
Weight	43 kg
Motor	TiMotion TA37 Protection rating IP66
Material	Powder-coated steel
Accessories	Single sling bar 370 mm, class 3 weighing scale, range of ProLift slings



**Compact, lightweight and functional, the novacare Cacero. German design and engineering make it an attractive choice for home care or institutional use.**

Its broad lifting range allows clients to be lifted from the floor, perfect for any care environment and covering a wide range of applications. The design of the undercarriage provides the client with space for a more relaxed transfer. The legs allow a wide spread to access large chairs or wheelchairs. The novacare Cacero can be folded down without using tools for easy transport and storage. The novacare Cacero with its low-friction, smooth rolling wheels uses the most advanced TiMotion control box, handset and actuator with a protection class of IP66. It has a low total weight of 43 kg promoting manoeuvrability but still allows a safe working load of 180 kg.

### Highlights

- On board charging and battery level indicator
- Handset with battery level indicator
- Audible warning for low battery status
- Low friction wheels
- Compact size for tight spaces and narrow corridors
- Easily folded for easy transport and storage
- High stability through robust construction
- Manual leg spreading
- Emergency stop and emergency lowering
- Possible to lift from floor
- Low undercarriage height
- Approx. 40 - 50 lifts per charge

